

DATASHEET

FEATURES:

- The ferrule is protected by the integrated spring-loaded shutter
- The connector housing protects the ferrule all round against dust, dirt and scratches
- No different expansion coefficients due to monoblock ceramic ferrule
- Color coding
- Latched push-pull locking type

APPLICATIONS:

- Telecommunication
- CATV
- LAN (including FITL, FTTH and FTTD)

E2000 / PC Specifications:

| Type | Singlemode | Multimode |
|------------------------------|---------------------------|---------------------------|
| Insertion Loss | ≤0.4dB (Typ 0.2) | ≤0.4dB (Type 0.2) |
| Return Loss | ≥50dB | ≥40dB |
| Repeatability | Max change ≤0.2 dB | Max change ≤ 0.2 dB |
| Durability | 1000 mate / demate cycles | 1000 mate / demate cycles |
| Operating Temperature | -25 C - 70 C | -25 C - 70 C |

E2000 / APC Specifications

| Type | Singlemode |
|------------------------------|---------------------------|
| Insertion Loss | ≤ 0.4 dB (Type 0.2) |
| Return Loss | ≥ 85 dB |
| Repeatability | Max change ≤0.2 dB |
| Durability | 1000 mate / demate cycles |
| Operating Temperature | -25 C - 70 C |

Other hybrid patchcords are available upon request.

